

Creating a new VisionScape Template

To create a template with just a single placeholder, simply copy and paste the below highlighted HTML code into your file as shown below.

```
<%@ Page language="c#" Codebehind="TemplateLoader.aspx.cs" AutoEventWireup="false"
Inherits="Redback.GlobalWMS.templates.TemplateLoader" %>
<%@ Register TagPrefix="ucl" TagName="navigation" Src="../Utilities/controls/navigation.ascx"%>
<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN">
<html>
<head>
<asp:Literal id="METADATADesc" runat="server"></asp:Literal>
<asp:Literal id="METADATAKeywords" runat="server"></asp:Literal>
<title>
<asp:Literal id="METADATATitle" runat="server"></asp:Literal>
</title>
<meta http-equiv="Content-Type" content="text/html; charset=iso-8859-1">
<link href="/SiteFiles/newcastlenetballcom/Styles/Styles.css" rel="stylesheet" type="text/css">
</head>
<asp:Literal id="PageConfig" runat="server">
  <!--
<VS_SITE>18</VS_SITE>
<VS_COMPONENTS>1</VS_COMPONENTS>
<VS_HOME_PAGE>308</VS_HOME_PAGE>
-->
</asp:Literal>
<body leftmargin="0" topmargin="0" marginwidth="0" marginheight="0">
<form id="Form1" runat="server">
  <ucl:navigation id="Navigation1" runat="server" SiteID="18" MenuType="js"></ucl:navigation>
  <table width="100%" height="100%" border="0" align="center" cellpadding="0" cellspacing="0">
    <tr>
      <td valign="top">
        <asp:Literal id="litStart1" runat="server"></asp:Literal>
        <asp:Placeholder id="Placeholder1" runat="server" />
        <asp:Literal id="litEnd1" runat="server"></asp:Literal>
      </td>
    </tr>
  </table>
</form>
</body>
</html>
```

The code highlighted with blue indicates variables that will need to be set by you.

- The `<VS_SITE>` variable is the site id for your template.
- The `<VS_COMPONENTS>` variable is the number of placeholders used on the page.
- The `<VS_HOME_PAGE>` variable is the default homepage for your website.

To create a template with multiple placeholders, you need to change the `<VS_COMPONENTS>` variable to the total number of placeholders on the page. For example, say we have a News, Events and HTML Block for our template. You first need to change the `<VS_COMPONENTS>` variable to 3. Then copy and paste the placeholder block and rename as shown below:

```
<asp:Literal id="litStart2" runat="server"></asp:Literal>
<asp:Placeholder id="Placeholder2" runat="server" />
<asp:Literal id="litEnd2" runat="server"></asp:Literal>
```

See below for a complete code listing for the new template:

```
<%@ Page language="c#" Codebehind="TemplateLoader.aspx.cs" AutoEventWireup="false"
Inherits="Redback.GlobalWMS.templates.TemplateLoader" %>
<%@ Register TagPrefix="ucl" TagName="navigation" Src="../Utilities/controls/navigation.ascx"%>
<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN">
<html>
<head>
<asp:Literal id="METADATADesc" runat="server"></asp:Literal>
<asp:Literal id="METADATAKeywords" runat="server"></asp:Literal>
<title>
<asp:Literal id="METADATATitle" runat="server"></asp:Literal>
</title>
<meta http-equiv="Content-Type" content="text/html; charset=iso-8859-1">
<link href="/SiteFiles/newcastlenetballcom/Styles/Styles.css" rel="stylesheet" type="text/css">
</head>
<asp:Literal id="PageConfig" runat="server">
  <!--
<VS_SITE>18</VS_SITE>
<VS_COMPONENTS>3</VS_COMPONENTS>
<VS_HOME_PAGE>308</VS_HOME_PAGE>
-->
</asp:Literal>
<body leftmargin="0" topmargin="0" marginwidth="0" marginheight="0">
<form id="Form1" runat="server">
  <ucl:navigation id="Navigation1" runat="server" SiteID="18" MenuType="js"></ucl:navigation>
  <table width="100%" height="100%" border="0" align="center" cellpadding="0" cellspacing="0">
    <tr>
      <td valign="top">
        <asp:Literal id="litStart1" runat="server"></asp:Literal>
        <asp:Placeholder id="Placeholder1" runat="server" />
        <asp:Literal id="litEnd1" runat="server"></asp:Literal>

        <asp:Literal id="litStart2" runat="server"></asp:Literal>
        <asp:Placeholder id="Placeholder2" runat="server" />
        <asp:Literal id="litEnd2" runat="server"></asp:Literal>

        <asp:Literal id="litStart3" runat="server"></asp:Literal>
        <asp:Placeholder id="Placeholder3" runat="server" />
        <asp:Literal id="litEnd3" runat="server"></asp:Literal>

      </td>
    </tr>
  </table>
</form>
</body>
</html>
```